

iFILTRATION® HF Series

The **iFILTRATION HF** series **High-Flow** filter cartridge (OD: 6 inches) is made of pleated multi-layer filter media. The outer cage, inner core, and cap are made of polypropylene. We use thermal melting technology for each seal without adhesives to prevent leakage and pollution and ensure a good sealing effect. The unique design allows for a high contaminant loading capacity for better depth filtration, provides reliable performance, optimizes the filtration area, dramatically reduces the number of filter cartridges and the filter housing size, and is widely used in various applications.

FEATURES

- · Pleated filter media design
- Large filtration area
- · Fewer number of filter cartridges
- High contaminant load capacity
- Polypropylene material for the outer cage, inner core, and end cap
- Stable performance
- · Inside out flow / Outside in flow
- Wide range of micron rating 1 100 μm
- High-quality polypropylene material in gradient density
- Holding debris effectively

APPLICATIONS

- Reverse Osmosis Pretreatment Filtration
- Condensate Water Filtration
- · Reclaimed Water Treatment
- Cooling Water Treatment
- Electronic Water Discharged Filtration



Materials of Construction

Media	Glass Fiber and Pleated Polypropylene
End Cap & Core	Polypropylene
Seal Options	NBR / EPDM / FKM / Silicone

Operating Limits

Max. Working Temperature	80°C (176°F)
Max. Operating ΔP	2.5 bar @ 20°C (68°F)
Recommended	2 bar @ 20°C (68°F)
replacement ΔP	

LENGTH	20"	40"	60"
RECOMMENDED DESIGN FLOW RATE	15 m³/h	30 m³/h	45 m³/h
MAX. FLOW RATE	30 m³/h	60 m³/h	90 m³/h

Model Selection

	SERIES	FILTER MEDIA	-	ENCY RATE**	END CAP	LENGT	H SEAL
iFILTRATION HF	D = iFILTRATION	PP	$0100 = 1 \ \mu m$	2000 = 20 μm	A1*B1*	20"	B = NBR
	C = Cobetter	GF	0200 = 2 μm	4000 = 40 μm	A2B2	40"	E = EPDM
			0300 = 3 μm	7000 = 70 μm	A3*B3*	60"	F = FKM
			0500 = 5 μm	9000 = 90 μm	A4*B3*		S = SILICONE
			1000 = 10 μm	100H =100 μm			
			1500 = 15 μm				

NOTE: • Impact Filtration will custom-make iFILTRATION HF filter cartridge as per request.

• The end cap may be combined based on customer needs.



TEL +1 (925) 477-8513

EMAIL sales@impactfiltration.com **W**EB www.impactfiltration.com

Doc. No. PDS-IF-2025-05-001-04-EN

©2025 Impact Filtration, Inc. All rights reserved. Impact Filtration reserves the right to modify the designs and specifications contained herein without prior notice.

Impact Filtration is the exclusive global distributor for Cobetter® products (excluding Australia, China, Cyprus and Oman)

Impact Filtration and iFILTRATION are registered trademarks of Impact Filtration. Cobetter is the registered trademark of Cobetter. ROPV is the registered trademark of ROPV.

> Please contact your local Impact Filtration sales representative for the most current information.